



PRODUCT DESCRIPTION

Dimensions	2038mm x 190mm
Thickness	9mm
Bevels	4
Loc System	5G Loc under licence of Välinge Innovation AB
Classification of use	Class 23/32 According to European Standard EN13329

	Contains	m ²	ft ²	Weight
1 pack	5 planks	1,94 m ²	20,84 ft ²	15,9 kg
1 pallet	72 packs	139,4 m ²	1500,48 ft ²	1173 kg

COMPOSITION

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF)
Backing	Direct laminated paper, impregnated with melamine resin

TESTED VALUE

Abrasion resistance
Impact resistance
Thickness swelling
Fire resistance
Formaldehyde
Slipperiness
Density
Resistance to staining
Resistance to cigarette burns
Effect of a furniture leg
Effect of a castor chair
Thermal resistance in combination with underlay Excellence Plus

METHOD

EN13329
EN13329
EN13329
EN14041
EN14041
EN14041
EN323
EN438
EN438
EN424
EN425

TEST RESULTS

AC4 (IP≥4000)
Small ball : ≥ 12 N - Big ball : ≥ 750 mm
12% (requirement ≤ 18%)
Cfl-S1
E1
DS
900 kg
5 (groups 1+2); 4 (group 3)
4
No damage (foot type 0)
No change in appearance or damage
0,09 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com

CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- CARB: Phase II compliant
- DOP : 170-DPLA18-1



WARRANTY

- Lifetime Residential Warranty
- 5 Years of Commercial Warranty
- Warranty conditions on www.berryalloc.com