

SMART 8 TECHNICAL DATASHEET



BERRYALLOC®
LAMINATE

PRODUCT DESCRIPTION

| | |
|-----------------------|--|
| Dimensions | 1288mm x 190mm |
| Thickness | 8mm |
| Bevels | - |
| Loc System | DuoLoc |
| Classification of use | Class 23/32 According to European Standard EN13329 |

| | Contains | m ² | ft ² | Weight |
|----------|----------|-----------------------|-------------------------|---------|
| 1 pack | 9 planks | 2,20 m ² | 23,71 ft ² | 15,7 kg |
| 1 pallet | 56 packs | 123,34 m ² | 1327,61 ft ² | 891 kg |

COMPOSITION

| | |
|---------------|---|
| Surface layer | Direct laminated paper, impregnated with melamine resin |
| Substrate | Moisture resistant High Density Fiberboard (HDF) |
| Backing | Direct laminated paper, impregnated with melamine resin |

TESTED VALUE

Abrasion resistance

Impact resistance

Thickness swelling

Fire resistance

Formaldehyde

Slipperiness

Density

Resistance to staining

Resistance to cigarette burns

Effect of a furniture leg

Effect of a castor chair

Thermal resistance in combination with underlay Excellence Plus

METHOD

EN13329

EN13329

EN13329

EN14041

EN14041

EN14041

EN323

EN438

EN438

EN424

EN425

TEST RESULTS

AC4 (IP≥4000)

Small ball : ≥ 12 N - Big ball : ≥ 750 mm

12% (requirement ≤ 18%)

Cfl-S1

E1

DS

900 kg

5 (groups 1+2); 4 (group 3)

4

No damage (foot type 0)

No change in appearance or damage


0,08 m²K/W – Suitable for floor heating/cooling.
Detailed instructions on www.berryalloc.com

CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- DOP : 170-DPLA18-1

WARRANTY

Lifetime Residential Warranty
5 Years of Commercial Warranty
Warranty conditions on www.berryalloc.com



WWW.BERRYALLOC.COM